

MATERIAL (ROHS COMPLIANT):

1. CABLE: UL1007 18AWG, OD:2.1MM COLOR: YELLOW X 1PC, BLACK X 2PCS, RED X 1PC

2. CONNECTOR :

SERIAL ATA 15P MALE, GOLD PLATED CONTACT


OVERMOLD: PVC 50P COLOR BLACK

3. CONNECTOR :

TERMINAL: 4PIN MALE 5.08" PITCH TIN-PLATED

HOUSING: 4PIN FEMALE 5.08" PITCH WHITE COLOR INSULATION

4. L = 220+/- 10MM



| P1 | P2 |
|----------|----------------|
| 1 YELLOW | 1 (1, 2, 3) |
| 2 BLACK | 2 (4, 5, 6) |
| 3 BLACK | 4 (10, 11, 12) |
| 4 RED | 3 (7, 8, 9) |

ELECTRICAL:

1. CONTACT RESISTANCE: 5 OHM (MAX.)

2. 100% OPEN, SHORT AND MIS-WIRING TEST

3. INSULATION RESISTANCE: 10 M OHM

| Itemref | Quantity | Title/Name, designation, material, dimension etc | | | Article No./Reference | |
|-------------|------------|--|--------------------------|---------------------|-----------------------|--|
| Designed by | Checked by | Approved by - date JAN.20,2011 | File name POWER CABLE | Date JAN.20,2011 | Scale FREE | |
| | | | 4PIN / SATA 15 | | | |
| | | | 26-1002RM | Edition 1 | Sheet 1/1 | |